# PELF LED PANEL LOW UGR

5 YR WAF



## **Key Features**

- •Slim profile LED Panel.
- •Available in 17W, 25W, 32W or 50W.
- •50,000 hours at L70.
- •CRI > 80.
- •Available in 4 different sizes.
- ·Mounting types include wire suspension, surface mount,
- plaster and T-bar.
- •Micro-prism (UGR19).
- •Aluminium frame with powder coated finish.
- •Comes with 1.2m flex and plug.
- •Non-dimmable and DALI dimming options available.

#### Accessories Plaster Frame Cable Single Cable Pair Surface Mount Frame Surface Mount Frame

## Dimensions







## Code

#### PELF-TB/32/12X3/40/ND

Product Series		Wattage (W) & Nominal				ССТ		EGC		
PELF-TB	T-Bar	17	17W	1600lm	6X3	600X300	30	3000K	ND	Non Dimming
PELF-PB PELF-SM	Plaster Surface Mount	25	25W	3000lm	12X3	1200X300	40 57	4000K 5700K	DALI	DALI Dimming
PELF-SM PELF-SSM	Shallow Surface	25	2377	3000im	12/23	1200/200	57	5700K		
	Mount	32	32W	3400lm	6X6	600X600				
PELF-SUS	Suspension	02	0211	0100111	12X3	1200X300				
		50	50W	5000lm	12X6	1200X600				

Specifications subject to change without notice

# PELF LED PANEL LOW UGR ACCESSORIES

## Plaster Frame

• Frame can be installed into plaster ceilings.

Specifications	6x3	6x6	12x3	12x6	
Length	625mm	625mm	1225mm	1225mm	
Width	325mm	625mm	325mm	625mm	
Depth	40mm	40mm	40mm	40mm	
Cut-out	610x310mm	610x610mm	1210x310mm	1210x610mm	



# Surface Mount Frame (Deep)

- Frame to be mounted in solid concrete ceilings.
- Designed to house both LED panel and driver.

• White powder coat finish.

Specifications	6x3	6x6	12x3	12x6	
Length	600mm	600mm	1200mm	1200mm	
Width	355mm	655mm	355mm	655mm	
Depth	66mm	66mm	66mm	66mm	



# Surface Mount Frame (Shallow)

- Frame to be mounted in solid concrete ceilings.
- $\cdot \mbox{Designed}$  to house LED panel only (driver must be remote).
- $\cdot$  White powder coat finish.

Specifications	6x3	6x6	12x3	
Length	600mm	600mm	1200mm	
Width	320mm	620mm	320mm	
Depth	30mm	30mm	30mm	



## Wire Suspended Kits

- 1.8m wire-steel.
- Suspension height can be adjusted
- Two suspension types available: I and Y. Type I for use with 595mm wide panel, 4 per panel. Type Y for use with 295mm wide panel, 2 per panel.



Bracket Kit



I-type Suspension Bracket Kit

