




Key Features

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- SELV.
- Future Proof Replaceable Gear Tray.
- Available in DALI Dim or Switch Dim.
- Available in Plaster Recessed, Surface Mount, Suspended, T-Bar recessed (38mm Standard T-Bar).
- Clinical Observation available upon request.
- Available with Rod or Wire Suspensions (OSIK-S Only).

Dimensions



Cutout Dimension	Fitting Dimension
315x295	297x295
596x311	597x295
1196x311	1190x295
605x605	597x590

Technical Information

Configurations	Non Dim System Wattage (W)	Combined Board Output (lm)	Dimensions (mm)
4x7.2W	33	4400	297x295
1x08W	10.6	1220	597x295
2x08W	22.2	2440	597x295 & 1200x295
3x08W	28.76	3660	597x590
4x08W	38.1	4880	1190x295 & 597x590
1x14W	17.62	2200	597x295
2x14W	34.34	4400	597x295 & 1190x295
3x14W	51.92	6600	597x590
4x14W	68.52	8800	1190x295 & 597x590

Code

OSIK-TB/4X14/12X3/LO/40/ND

Product Series		# of boards		Wattage of Boards		Nominal Dimensions		Diffuser Type		CCT		Driver	
OSIK-TB	T-bar	1	1 Board	07	7W	3x3	300x300	LO	White Acrylic	30	3000K	ND	Non Dimming
OSIK-PB	Plaster	2	2 Board	08	8W	6x3	600x300	MP	Microprism	40	4000K	DALI	DALI Dimming
OSIK-S	Surface Mount	3	3 Board	14	14W	6x6	600x600					SD	Switch Dimming
		4	4 Board			12x3	1200x300						

See Technical Information Table for configurations options.
Specifications subject to change without notice

