

VEKTA VHB1717



Key Features

- Minimum bend diameter = 150mm
- UV resistant
- 120 degree beam angle
- Horizontal Bend
- Maximum length 5m
- Other colour outputs available on request
- 100mm Cut length
- 71.4mm incremental cut length for RGBW
- 7m max single feed length for RGBW

Compliance



Code

Example:

VHB1717-S109040DEDO-2400


Profile	Mounting	Power	CRI	CCT	Connector	Driver	Length
VHB1717	S - Surface Mount	10 - 10 W/m (365lm/m)* 15 - 15 W/m RGBW ONLY	80 - CRI>80 90 - CRI>90***	22 - 2200K 27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K 45 - 4500K 50 - 5000K 65 - 6500K RE - Red GR- Green BL - Blue RGBW27K RGBW3K RGBW4K	DE - Direct SE - Side entry BE - Bottom JU - Jumper	DO - Non-Dim DA - Dali-Dim SW - Switch-Dim CA - Casambi D4 - DALI RGBW C4 - CASAMBI RGBW	- XXXX mm

* Based on CRI>80 and 4000K


***MOQ on CRI>90

Mounting


Surface Mounted (S)



Flex Direction



Mounting Channel



* Mounting Channel image is for reference and may change from strip to strip.

Dimensions

