

RDL-LED


LED RADIAL



Key Features

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Future proof replaceable gear tray.
- Powder coated white metal body - other colours available upon request.
- Available in DALI dim or switch dim.
- Choice of two wrap around diffusers: High transmittance K5 patterned and K19 prismatic diffuser.
- Self hinged lens for ease of cleaning.
- Suitable for fixing directly to ceiling or may be rod suspended.
- Suitable for in-line mounting.

Dimensions



Technical Information

Configurations	Non Dim System wattage	Combined Board Output (lm)	Length (mm)
1x08W	10.6	1220	575
2x08W	22.20	2440	575 & 1175
4x08W	38.10	4880	1175
1x14W	17.62	2200	575
2x14W	34.34	4400	575 & 1175
4x14W	68.52	8800	1175

Code

RDL-LED/2X08/06/K19/40/ND

Product Series	# of boards		Wattage (W)		Nominal Length		Diffuser Type		CCT		Driver	
			08	8W	06	600	K19	K19 Prismatic	30	3000K	ND	Non Dim
RDL-LED	1	1 Board	14	14W	12	1200			40	4000K	DALI	DALI Dim
	2	2 Board									SD	Switch Dim
	4	4 Board										

See Technical Information Table for configurations options
Specifications subject to change without notice

